WITH 16 FRESH COLOR-WAYS IN A FLOWING GRAIN PATTERN, THE **AVA SNSE** COLLECTION IS OFFERED IN 8 SATURATED COLORS WITH 8 COMPLEMENTARY NEUTRALS.



- WEAR LAYER: 20 MIL
- THICKNESS: 2.5 MM • SIZE: 12" X 24"
- 100% PHTHALATE FREE
- REACH COMPLIANT
- WARRANTY: 10 YEAR COMMERCIAL WARRANTY
- PRODUCT STRUCTURE:

TRANSPARENT WEAR LAYER: EXTREMELY DURABLE WITH PURITY VINYL WEAR LAYER

PRINTED WEAR LAYER: THIS DESIGN LAYER GIVES THE FLOOR ITS UNIQUE PATTERN AND COLOR

PU COATING: EXCELLENT STAIN, ABRASION AND FADE RESISTANCE WITH ANTI-BACTERIAL EFFECT, EASY TO MAINTAIN AND NO NEED TO WAX

IDDLE LAYER: HIGH PERFORMANCE VINYL LAYER THAT PROVIDES EXTRA STABILITY AND DURABILITY TO

GLASS FIBER LAYER (FOR LOOSE LAY AND CLIC ONLY): MINIMIZES THE EXPANSION AND CONTRACTION OF

BACKING LAYER: VINYL BACKING, HIGH RESISTANCE TO PRESSURE AND ECO-FRIENDLY PERFORMANCE

ANTI-SLIP LAYER (FOR LOOSE LAY ONLY): ALLOWS PRODUCT TO BE INSTALLED WITHOUT ADHESIVE AND TO BE EASILY REMOVED AND REPLACED






OTHER PRODUCTS IN THE AVA COLLECTION: AVA DSGN™ & AVA STYL™

WITH WORLDWIDE SALES OFFICES AND DISTRIBUTION PARTNERS, NOVALIS IS A LEADER IN THE DESIGN AND MANUFACTURING OF INNOVATIVE AND SUSTAINABLE LUXURY VINYL FLOORING. ESTABLISHED IN 1984, NOVALIS HAS DEVELOPED A DIVERSE RANGE OF DESIGNS AND PRODUCTS THAT HAVE WON NUMEROUS AWARDS AND ARE RECOGNIZED BY THE INDUSTRY AS SETTING THE BENCHMARK IN LVT.

AVA™, STYL™, DSGN™, AND SNSE™ ARE TRADEMARKS OF NOVALIS INNOVATIVE FLOORING. © 2015 NOVALIS INNOVATIVE FLOORING









AVA SNSE



ALL AVA SNSE COLORS ARE READILY AVAILABLE THROUGH OUR USA QUICK-SHIP PROGRAM.

THE PERFECT LONG-TERM FLOORING SOLUTION FOR HEAVY TRAFFIC AREAS INCLUDING AREAS WITH HEAVY ROLLING LOADS, AVA SNSE IS SUITABLE FOR VIRTUALLY ALL COMMERCIAL SECTORS WITH AN EMPHASIS ON EDUCATION AND HEALTHCARE.

IFICATIONS:	
1 F1700-13 SOLID VINYL FLOOR TILE:	CLASS III, TYPE B
D2047 STATIC COF FOR POLISHED SURFACES:	EXCEEDS INDUSTRY STANDARDS
1 F970-07 STATIC LOAD LIMIT:	PASSES (MODIFIED EXCEEDS 1000 LBS PSI)
1 E648 CRITICAL RADIANT FLUX:	CLASS 1
1 E662 SMOKE DENSITY:	PASSES
1 F925 STAIN & CHEMICAL RESISTANCE:	EXCELLENT













